


RINSE-AID ADDITIVE FOR DISHWASHER RINSE CYCLES



- Always guarantees sparkling and dry dishware.
- A product specifically for the drying cycle for dishware.
- Facilitates the running-off of water, avoiding the formation of marks.



SUGGESTIONS

For best results, BRILLMATIC TE must be used in the indicated dosages

DESCRIPTION

According to the HACCP sanitising programme, after every wash carried out with a dishwasher, it is necessary to pay the utmost attention in order to not contaminate the clean dishes with dirty and non-disinfected cloths.

For this reason, it is necessary to use a specific product for the drying cycle for dishware, plates and glasses, rendering additional manual finishing unnecessary.

BRILLMATIC TE allows for the perfect drying of dishware by facilitating the running-off of water and inhibiting the formation of marks, lime scale stains and white streaks.

It acts during the rinse cycle, guaranteeing sparkling dishware every time, restoring plates and glasses to their original splendour.


It guarantees the highest level of hygiene, limiting the bacterial load, for perfect washing results.

Ideal for the mechanical washing of dishware, above all in glass washing mac

RINSE-AID ADDITIVE FOR DISHWASHER RINSE CYCLES

PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance	Clear liquid
Colour	Light blue
Fragrance	Weak characteristic
Specific weight	0.985 ± 0.015 g/ml
Solubility in water	Complete in all ratios
pH	2.5 - 3
Chemical properties	Nonionic



Low

AVAILABLE PACKAGING

5 kg container - 016BLMA5005 (2 pieces carton)
20kg container - 016BLTETN20

USE MODALITY

BRILLMATIC TE must be mixed with the water for the final rinse cycle, with an average dosage of 0.30 ml/L.

In cup washers fitted with a small dosage group for rinse-aid, it is sufficient to have the drawing tube draw directly from the product container; otherwise, it is necessary to fill the appropriate tank, following the usage instructions for the dishwasher.

In industrial-type dishwashers, for the best results, it is necessary to install the dedicated automatic dosage units which guarantee the correct dosing.

FOR PROFESSIONAL USE ONLY.

The product maintains its properties when properly stored in an unopened package, in a cool and dry place away from light and heat sources, at a temperature between 5°C and 35°C.

CORRELATED PRODUCTS ACCESSORIES

Pompa NPR-1 per
brillantante
01AA750055



Stovilmatic plus lemon
016SPLE0024



Disincrostante per
lavastoviglie
016DISL0020



Stovilmatic liquido te
016SOVS5020

