

DYNAMIC DEWAXING DETERGENT FOR FLOORS AND HARD SURFACES



- Controlled foam.
- Contains water-soluble solvents.
- Efficient both as a detergent and for the removal of wax.



SUGGESTIONS

Particularly recommended for the removal of ink stains and black marks left by the wheels of fork-lift trucks.

DESCRIPTION

Controlled foam liquid detergent for the cleaning and dynamic degreasing of floors not protected by wax. Suitable for the daily cleaning and maintenance of particularly hard-to-clean stoneware surfaces. Appropriately diluted, it is an excellent dewaxing agent for floors.

DYNAMIC DEWAXING DETERGENT FOR FLOORS AND HARD SURFACES

PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance	Clear liquid
Color	Yellowish
Fragrance	Mild and characteristic
Specific weight	1.050 ± 0.01 g/ml
Solubility in water	Complete at any ratio
pH	> 13
Chemical properties	Nonionic



Low

AVAILABLE PACKAGING

5 kg can in 2 pieces carton - single product code - 016K1000005

USE MODALITY

For manual cleaning operations.
Dilute from 0.5% to 1% in water.
Increase the dosage to 5% in cases of stubborn dirt.
Apply the solution with a mop, and leave on if necessary. Rinse the floor with clean water.

Machine cleaning operations.
Dilute from 0.5% to 3% in water.
Prepare the solution in the tank of the single-brush floor machine or washer-dryer machine. Rub the solution into the floor. Rinse with clean water or vacuum.

Dewaxing operations:
Dilute from 10% to 20% in water.
Spread the solution evenly and generously. Leave on for 10 - 20 minutes (do not allow to dry). Brush with a single-brush floor machine fitted with a suitable disc. Vacuum the solution and rinse.

Removal of black marks:
Dilute from 20% to 30% in water.
Apply the solution to the marks to be removed.
Leave on for a few minutes. Pass with a single-brush floor machine fitted with a suitable disc. Rinse.

FOR PROFESSIONAL USE ONLY.

The product maintains its properties when properly stored in an unopened package, in a cool and dry place away from light and heat sources, at a temperature between 5°C and 35°C.


K 100

allegrini.
HO.RE.CA. & FACILITIES

DYNAMIC DEWAXING DETERGENT FOR FLOORS AND HARD SURFACES

CORRELATED PRODUCTS ACCESSORIES

Telaio lock
01AA770672



Panno wet system micro
blue
01AA770670



Carrello Witty 30L con
strizzatore
01AA770679



Teralux
016TELU0020



P28 Emulsio
016P28E0010



Rev. 02 Ed. 05/23